

## INDUSTRIAL VACUUM CLEANERS

### W 3 - Single phase industrial vacuum cleaner - INDUSTRIAL SINGLE PHASE



CHEMICAL-PHARMACEUTICAL



CLEANING CONTRACTORS



TEXTILE



TIMBER INDUSTRY



Accessories included. Ideal for cleaning contractors.

Single phase Industrial vacuum cleaner. Integrated manual filter cleaning system.

Easy material discharge by detachable container on wheels.

100% steel construction.

Suitable for wet and dry service, also simultaneously.

Detachable container with direct bagging option.

Proven for use in the woodworking industry

Anti-Static M Class filter as standard, with wide filtration surface for fine dusts.



#### SUCTION UNIT

Voltage	V - Hz	230
Power	kW	3 x 1.1
Max Pressure	Pa	24,000
Max air flow (at inlet)	m <sup>3</sup> /h	540 (400)
Suction inlet	mm	80 (50mm Tools)



#### FILTER UNIT

Filter Type		Star
Surface - Diameter	cm <sup>2</sup> -mm	20,000
Cleaning system		Manual



#### COLLECTION UNIT

Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	65 (100Ltr Option)



#### VOLUME

Dimensions	cm	58 x 60 x 135h
------------	----	----------------

Product Code: **INDUS/VAC/W3**





## SUCTION UNIT

Suction is developed by three carbon brush by-pass motors which are activated by independent switches placed on a solid, metallic head. Special noise buffers reduce the noise within the safety work standards.



## FILTER UNIT

The polyester star filter with large filtration surface is placed inside the filter chamber.

Ensuring protection from dust and avoids filter clogging.

The filter is cleaned mechanically by means of a manual filter shaking lever which shakes the filter vertically, ensuring safe and effective cleaning. This contributes to maintain high suction efficiency and avoids the spreading of dust in the environment.



## COLLECTION UNIT

Suctioned material deposits inside an extractable steel container fitted with wheels, allowing practical and safe emptying. Use with disposable bags is possible when purchased with a retaining ring.



## OPTIONALS

- ✓ Nomex heat resistant filter up to 250°
- ✓ Stainless steel collection tank
- ✓ Stainless steel collection tank and filter chamber
- ✓ Earth grounding



Phone: 0333 9967 333

Email: [mail@indusvent.com](mailto:mail@indusvent.com)